

FALCON LED Street Light



**5 YEAR
WARRANTY**

Areas of application

- Urban roads -
- Express roads -
- Town roads -
- Residential area roads -
- Pedestrian crossings -
- Parking areas -



Product Benefits

- 70% energy saving, short ROI period
- Up to 100,000hrs @ L70, low maintenance cost
- World class, approbated quality components (LEDs /Driver /etc.)
- Support horizontal and vertical mounted, suitable for different light poles
- Tool-less opening of driver box, ease of maintenance
- 5 years warranty

Product Features


- Luminaire efficacy: Up to 195 lm /w
- Lifetime more than 100,000 hours
- Impact resistance: IK09 /IK10
- Type of protection: IP66



Product Datasheet

Version S


Model No		2070M-5T19-10W	2070M-5T19-30W	2070M-5T19-50W	2070M-5T19-60W
Nominal Wattage		10W	30W	50W	60W
2070 version	Efficiency Lumen	150 lm/w 4500 lm	155 lm/w 4650 lm	160 lm/w 4800 lm	160 lm/w 4800 lm
3050 version	Efficiency Lumen	160 lm/w 4800 lm	165 lm/w 4950 lm	165 lm/w 5050 lm	165 lm/w 5050 lm
Ultra Version	Efficiency Lumen	170 lm/w 5100 lm	183 lm/w 5490 lm	183 lm/w 5550 lm	176 lm/w 52500 lm
Net Weight (Kgs)		4.0	4.0	4.0	4.0
Packing Size (mm)		480 x 310 x 175	480 x 310 x 175	480 x 310 x 175	480 x 310 x 175
Gross Weight (Kgs)		4.7	4.7	4.7	4.7



Version S

Version M


Model No		Z65M-5T19-60W	Z65M-5T19-100W
Nominal Wattage		60W	100W
2070 version	Efficiency Lumen	150 lm/w 12000 lm	165 lm/w 14500 lm
3050 version	Efficiency Lumen	160 lm/w 12800 lm	160 lm/w 14000 lm
Ultra version	Efficiency Lumen	176 lm/w 14080 lm	176 lm/w 14560 lm
Net Weight (Kgs)		4.4	4.4
Packing Size (mm)		545 x 310 x 175	545 x 310 x 175
Gross Weight (Kgs)		5.0	5.0



Version M

Version L


Model No	Z65M-5T19-100L	Z65M-5T19-160L	Z65M-5T19-120L	Z65M-5T19-150L
Nominal Wattage	100W	160W	120W	150W
1070 version	Efficiency Lumen	160 lm/w 16000 lm	165 lm/w 16500 lm	165 lm/w 16500 lm
2070 version	Efficiency Lumen	165 lm/w 16500 lm	165 lm/w 16500 lm	165 lm/w 16500 lm
Ultra Version	Efficiency Lumen	192 lm/w 19200 lm	195 lm/w 19500 lm	194 lm/w 19400 lm
Net Weight (Kgs)	6.0	6.0	6.0	6.0
Packing Size (mm)	610 x 365 x 175	610 x 365 x 175	610 x 365 x 175	610 x 365 x 175
Gross Weight (Kgs)	6.7	6.7	6.7	6.7



Version L

Version XL

Model No		2070M-5T19-150W	2070M-5T19-180W	2070M-5T19-200W
Nominal Wattage		150W	180W	200W
2070 version	Efficiency Lumen	160 lm/w 24000 lm	165 lm/w 27000 lm	165 lm/w 33000 lm
3050 Version	Efficiency Lumen	170 lm/w 25500 lm	165 lm/w 27000 lm	165 lm/w 33000 lm
Ultra Version	Efficiency Lumen	180 lm/w 27000 lm	177 lm/w 31000 lm	176 lm/w 33000 lm
Net Weight (Kgs)		6.8	6.8	6.8
Packing Size (mm)		665 x365x175	665 x365x175	665 x365x175
Gross Weight (Kgs)		7.6	7.6	7.6



Version XL

*Above values are calculated based on the product with CCT over 3000K, values of 3000K are 5% lower than above values.
 *Actual values are subject to 5% tolerance.
 *Model No with "T" means high efficiency version.

Product Datasheet


Electrical Data :

Nominal Voltage	AC 100-240V / 2.2/7/50/60Hz
LED	Dimmable / Other available on request
Driver	meatronics / Other available on request
Power Factor (PF)	>0.95
THD	<15
SPD	100% (Default) / 200% (available on request)
Optics	Type I, Type II, Asymmetric for pedestrian crossings
CR	Ra>70 (Default) / Ra>80
CCT	1800K, 2000K, 2700K, 3000K, 4000K, 5000K, 5600K, 6500K

General Data


Body Material	High pressure die-cast aluminum
Housing Color	Gray-PA-9007 (Default) / Other Colors on request
Cover Material	tempered glass
Lens Material	UV-resistan Polycarbonate
Working Environment	-40°C ~ +60°C, 10% ~ 90%RH
Life span (L70 at 25 °C)	>100,000 h
Mounting type	side entry drive vertical pole mounted
Dimmable	1-10V Dimming (Default) / Triac Dimming / DALI Dimming
Protection Class	Class I (Default) / Class II
Certifications & standards	UL, RoHS, ENEC, ENEC+, CE, LVD, UNBS, IEC62471, IEC60598-2-0, IEC60598-1, Zhaga-D4i
Available on request	NEHA socket (3/5/7 pins), Z-456A socket, Short-circ, Photoeye, Motion sensor, Knife switch, YTC, DLC, Solar Compatible, Smart Controller

Flexible Fitter



Product Datasheet

Structure Drawing:



Optional accessories



Photocell



Shorting Cap



NEMA Socket
(3 /5 /7pin)



Motion Sensor



Smart Controller



Knife switch



ZHAGA Socket



50-40mm



Square to round



T-type



L-type



2 in 1



4 in 1




80 mm filter


Product Datasheet

Light Distributions



Order reference



3030 Version



5050 Version



Packaging

